

# DATA SHEET



# ALL POS SYSTEM

## RECOMMENDED APPLICATIONS



FOOD SERVICES



RETAIL



ENTERTAINMENT



SERVICES



EDUCATION



£

HEALTHCARE



PUBLIC SECTOR



### POS-D WARRANTY

Don't forget to register this product on our warranty platform to obtain an **additional year of warranty** and benefit from a total of **2 years warranty** against manufacturing defects.

# DATA SHEET ALL POS 14W

#### SYSTEM

PROCESSOR	2.0 GHz Intel Celeron Quad Core Bay Trail J-1900
RAM MEMORY	4GB DDR3 expandable to 8GB
LOGIC CORE	Intel Bay Trail
NETWORK	10M/100M/1000M Base-T Fast Ethernet
DESIGN	100% FANLESS
SUPPORTED OPERATING SYSTEM	Windows 7, 8, 10, POS Ready 7

#### STORAGE

HARD DISK **SSD** 

SATA 128 GB

#### INPUT AND OUTPUT PORTS

SERIAL PORTS	3 external COM / 2 internal with 5 volts and 12 volts
USB PORTS	5 external
ETHERNET PORT	RJ-45 10/100/1000
VGA PORT	1 DB-15
CASH DRAWER	1 RJ-11 (12 volts)
DC-IN	12 volts DC-IN
POWER SWITCH	1 power switch

#### SCREEN

LCD	14" TFT LCD Widescreen Panel
MAXIMUM RESOLUTION	1366 x 768
BRIGHTNESS	300 nits
TOUCH SCREEN	Flat Touch Screen, 5-wire, Capacitive Panel
DISPLAY FRAME	Bezel Free
RACKABLE	No

#### ACCESSORIES

INCLUDED	Thermal ticket printer 3" wide, 180 mm/sec, 80x80 roll
	Customer display green LED light 2 rows of 20 characters each
OPTIONALS	Second 9.7" or 14" LCD rear display NO touch screen
	Magnetic stripe reader with 3-track reading
	Barcode scanner on the side of the monitor
	Integrated Wifi

#### PHYSICAL CHARACTERISTICS

PRODUCT DIMENSIONS	30.5 cms (Width) x 20 cms (Depth) x 38 cms (Height)
PRODUCT WEIGHT	5 kgs
BOX DIMENSIONS	55 cms (Width) x 28 cms (Depth) x 43 cms (Height)
WEIGHT WITH BOX	5.6 kgs.

#### **ENVIRONMENT CONDITIONS**

CASE	Aluminum
OPERATIONS	$0^\circ\text{C}$ to $40^\circ\text{C}$ / 20% humidity to 90% humidity max.
STORAGE	-20°C to 60°C / 10% humidity up to 90% max. humidity

#### SECURITY

SAFETY STANDARDS

CCC / CE / FCC

#### CONTENTS OF THE BOX

INCLUDED

ALL POS 14W All in one POS system, power supply, power cable, user manual, warranty certificate

#### WARRANTY

STANDARD WARRANTY POS-D WARRANTY

#### 1 Year against manufacturing defects.

2 Years against manufacturing defects, subject to product registration in our warranty registration platform at the following link: www.pos-d.com/en/pos-dwarranty



www.pos-d.com