

# DATA SHEET



**ALL IN ONE POS SYSTEM** 

**RANGER 68** 

## RECOMMENDED APPLICATIONS



FOOD SERVICES



RETAIL



ENTERTAINMENT



SERVICES



EDUCATION



HEALTHCARE



PUBLIC SECTOR

### CONNECTIVITY





USB



RJ 45



VGA



RJ 11

# POS-D WARRANTY

Don't forget to register this product on our warranty platform to obtain an **additional year of** warranty and benefit from a total of **2 years warranty** against manufacturing defects.

## DATA SHEET RANGER 68

#### SVSTEM

PROCESSOR Intel Celeron Quad Core Bay Trail J-1900

PAM MEMORY 4GB expandable to 8GB

LOGIC CORE Intel Bay Trail

10M/100M/1000M Base-T Fast Ethernet NETWORK

DESIGN 100% FANLESS

SUPPORTED OPERATING SYSTEM Windows 7, 8, 10, POS Ready 7

#### STORAGE

HARD DISK

SATA 128 GB SSD

#### INPUT AND OUTPUT PORTS

SERIAL PORTS 3 external COM

**USB PORTS** 4 external: 3 USB 2.0.1 USB 3.0

RJ-4510/100/1000 ETHERNET PORT

VGA PORT 1 DB-15 CASH DRAWER 1 RJ-11 (12 volts) DC-IN 12 volts DC-IN POWER SWITCH 1 power switch

#### SCREEN

LCD 15" TFT LCD Panel MAXIMUM RESOLUTION 1024 x 768 BRIGHTNESS 300 nits

**TOUCH SCREEN** Flat Touch Screen, 5-wire, Resistive Panel

DISPLAY FRAME Rezel Free

RACKABLE Disassembling the support base

#### ACCESSORIES

INCLUDED Power supply, power cable

OPTIONALS Customer display green LED light 2 rows of 20 characters each

> Magnetic stripe reader with 3 tracks reading Non-touch customer facing screen 10" LCD

#### PHYSICAL CHARACTERISTICS

PRODUCT DIMENSIONS 38.4 cms (Width) x 19.4 cms (Depth) x 32.4 cms (Height) PRODUCT WEIGHT

BOX DIMENSIONS 50 cms (Width) x 30 cms (Depth) x 45 cms (Height)

WEIGHT WITH BOX 6.5 kgs.

#### **ENVIRONMENT CONDITIONS**

Resistant ABS plastic with aluminum support base **OPERATIONS** 0°C to 40°C / 20% humidity to 90% humidity max. STORAGE -20°C to 60°C / 10% humidity to 90% humidity max.

#### SECURITY

SAFETY STANDARDS CCC / CE / FCC

#### **CONTENTS OF THE BOX**

INCLUDED RANGER 68 All in one POS system, power supply, power cable, user manual, warranty certificate

#### WARRANTY

STANDARD WARRANTY 1 Year against manufacturing defects.

2 Years against manufacturing defects, subject to product registration in our warranty registration platform at the following link: POS-D WARRANTY

www.pos-d.com/en/pos-dwarranty



www.pos-d.com